


DATA SHEET DOOR DETECTOR 03.G5.P154



Max. number of beams	154
Sensors	32
Effective distance	0-4000mm
Lowest beam	20mm
Uppermost beam	1841mm
Distance of sensors	58.80mm
Light immunity	sunlight proof
TH	2000mm, Min.1950mm, Max.2780mm
Profile material	Aluminium
Protection level	IP54
Operation temperature	-20°C - +65°C
Tolerance	Vertical: +/- 20mm(10°) Horizontal: +/- 3mm(7°)
Response time	57ms
Power consumption	<=4w or 100mA@DC24V
Signal output	Relay contact: 1 NO & 1 NC
LEDs in receiver	yellow Power indicator
	Red Beams interrupted or system fault
	Normal
Power supply	10-30 VDC
	100VDC
	230 VAC +/- 15%, 50 / 60Hz

Norms	EN81 - 70
EMV - Emission	EN12015
EMV - Immunity	EN12016
QMS	ISO 9001
EMS	ISO 14001
Cable length	
WECO Standard	3250mm (250 + 3000)
Optional	2750mm (250 + 2500)
	3750mm (250 + 3500)
	4250mm (750 + 3500)
	5250mm (250 + 5000)
Red	+
Black	-
Yellow	Synchro
Green	Output
Cable diameter	Ø5.9mm
Material	PVC
Fixing bracket size	see additional technical sheet
Fixing bracket quantity	10 pieces per set